

## **PAK 100 / PAK 130 / PAK 320**

The high performance Romaco Promatic PAK 320 is designed for packing cartons and/or bundles into RSC cases and features: a high capacity case magazine fitted with automatic lifting of the case to working height, forced case erection by means of a double arm equipped with suction cups and Venturi vacuum unit, closing of the flaps at the base of the case before the cartons are inserted. The case packer's operating processes and work areas such as stacking from bottom to top, transfer and subsequent insertion of the cartons into the case, are kept separated and allow checking of critical operations, reducing machine downtime to a minimum.

The Romaco Promatic PAK 130 is the ideal solution for data aggregation in a cost-effective and user-friendly, compact solution.

### **Highlights**

- Reduced downtime, cleaning and maintenance operations
- Clear view of product flow, immediate safe access to all functions and operations, high efficiency level
- GMP design
- Ergonomic design
- Machine errors' diagnosis and troubleshooting functions enhance operation of the machine
- Quick and easy changeover



### Romaco Promatic PAK 100 semi-automatic case-packer

The Romaco Promatic Pak 100 offers reliability and efficiency for simple applications. It removes time consuming steps of the packing process by automatically stacking and inserting cartons into manually opened cases.

### Highlights

- Compact and economical
- Equipped with PLC and LCD
- Simple design and user-friendly operations
- Compliant to European safety directives
- Optional automatic taping system

Technical Data	PAK 320		PAK 100		PAK 130	
	min.	max.	min.	max.	min.	max.
Mechanical speed (cases/min.)	8		5		5	
Power consumption (kW)	4		1.6		3	
Air consumption (NI/min.)	250		100		75	
Basic machine dimensions (mm), L x W x H	4,350 x 1,850 x 1,715		2,370 x 1,685 x 1,900		2,700 x 2,225 x 1,900	
Weight approx. (kg)	1,800		700		700	
<b>Carton size range (mm)</b>	<b>min.</b>	<b>max.</b>	<b>min.</b>	<b>max.</b>	<b>min.</b>	<b>max.</b>
A	20	180	20	210	20	210
B	15	100	15	85	15	85
C	60	210	60	210	60	250
<b>Case size range (mm)</b>	<b>min.</b>	<b>max.</b>	<b>min.</b>	<b>max.</b>	<b>min.</b>	<b>max.</b>
a3	200	500	230	550	230	550
b3	150	350	160	500	140	500
c3	120	350	150	350	150	350



TRIMACO Systeme GmbH | Badenerstrasse 816 | CH-8048 Zürich  
 Tel: +41 43 811 75 00 | [contact@trimaco.ch](mailto:contact@trimaco.ch)  
[www.trimaco.ch](http://www.trimaco.ch)

